

Specifications

Recommended drive chain lubricant	Drive chain lubricant designed specifically for O-ring chains. If not available, use SAE 80 or 90 gear oil.	
Drive chain slack	25 to 35 mm (1.0 to 1.4 in)	
Standard drive chain	DID 520V0 or RK 520KHO	
	CTX700A	No. of links 114
	CTX700D	No. of links 112
Standard sprocket sizes	Engine sprocket 16T	
	Rear wheel sprocket	
	CTX700A	43T
CTX700D	39T	

■ Bulbs

Headlight	12V-60/55W
Brake/Tail light	LED
Front turn signal lights	12V-21/5W × 2
Rear turn signal lights	12V-21W × 2
License plate light	12V-5W

■ Fuses

Main fuse	30A
Other fuses	30A, 15A, 7.5A

■ Torque Specifications

Engine oil drain bolt	30 N·m (3.1 kgf·m, 22 lbf·ft)
Engine oil filter	26 N·m (2.7 kgf·m, 19 lbf·ft)
Front wheel axle shaft	74 N·m (7.5 kgf·m, 55 lbf·ft)
Front wheel brake caliper mounting bolts	30 N·m (3.1 kgf·m, 22 lbf·ft)
Front wheel axle pinch bolt	22 N·m (2.2 kgf·m, 16 lbf·ft)
Muffler end cover bolts	10 N·m (1.0 kgf·m, 7 lbf·ft)
Rear wheel axle nut	98 N·m (10.0 kgf·m, 72 lbf·ft)
Drive chain adjusting lock nuts	21 N·m (2.1 kgf·m, 15 lbf·ft)
Parking brake caliper mounting bolts	31 N·m (3.2 kgf·m, 23 lbf·ft)