

| | | |
|-----------------------------------|-----------------------------|-----|
| Recommended drive chain lubricant | Pro Honda HP Chain Lube | |
| Drive chain slack | 1.0 to 1.4 in (25 to 35 mm) | |
| Standard drive chain | DID50ZVM2 or RK50LF0Z2 | |
| | No. of links | 110 |
| Standard sprocket sizes | Engine sprocket | 18T |
| | Rear wheel sprocket | 39T |

■ Bulbs

| | | |
|--------------------------|-------------|--|
| Headlight | 12V-60/55W | |
| Brake/Tail light | 12V-21/5W | |
| Front turn signal lights | 12V-21W x 2 | |
| Rear turn signal lights | 12V-21W x 2 | |

■ Fuses

| | | |
|-------------|----------------|---------------|
| Main fuse | 30A | |
| Other fuses | CB1100 | 20A, 10A |
| | CB1100A | 30A, 20A, 10A |

■ Torque Specifications

| | |
|--|---------------------------------|
| Engine oil drain bolt | 22 lbf·ft (30 N·m, 3.1 kgf·m) |
| Oil filter | 19 lbf·ft (26 N·m, 2.7 kgf·m) |
| Front wheel axle bolt | 43 lbf·ft (59 N·m, 6.0 kgf·m) |
| Front wheel brake caliper mounting bolts | 23 lbf·ft (31 N·m, 3.2 kgf·m) |
| Front wheel axle pinch bolts | 19 lbf·ft (26 N·m, 2.7 kgf·m) |
| Rear wheel axle nut | 83 lbf·ft (113 N·m, 11.5 kgf·m) |