

Specifications

■ Service Data

Tire size	Front	120/70-12 51L
	Rear	130/70-12 56L
Tire type	Bias-ply, tubeless	
Recommended Tires	Front	VEE RUBBER V119C
	Rear	VEE RUBBER V119C
Tire air pressure	Front	29 psi (200 kPa, 2.00 kgf/cm ²)
	Rear	29 psi (200 kPa, 2.00 kgf/cm ²)
Spark plugs	(standard)	CPR6EA-9 (NGK) or U20EPR9 (DENSO)
	(For extended high speed riding)	CPR7EA-9 (NGK) or U22EPR9 (DENSO)
Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)	
Idle speed	1,400 ± 100 rpm	

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving or resource conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil, or an equivalent motorcycle oil	
	Engine oil capacity	After draining 1.0 US qt (0.9 liters) After disassembly 1.2 US qt (1.1 liters)
Recommended brake (clutch) fluid	Honda DOT 3 or DOT 4 Brake Fluid	