Specifications

■ Main Components

Overall length	69.1 in (1,755 mm)		
Overall width	28.7 in (730 mm)		
Overall height	39.4 in (1,000 mm)		
Wheelbase	47.2 in (1,200 mm)		
Minimum ground clearance	6.1 in (155 mm)		
Caster angle	25°		
Trail	3.2 in (81 mm)		
Curb weight	GROM125 229 lb (104 kg)		
	GROM125A 234 lb (106 kg)		
Maximum weight capacity *1	309 lb (140 kg)		
Passenger capacity	Rider and 1 passenger		
Minimum turning radius	6.2 ft (1.9 m)		

^{*1:} Including rider, passenger, all luggage, and accessories.

Displacement	7.6 cu-in (125 cm ³)		
Bore x stroke	2.06 x 2.28 in (52.4 x 57.9 mm)		
Compression ratio	9.3 : 1		
Fuel	Unleaded gasoline		
	Recommended: 86 PON or higher		
Tank capacity	1.51 US gal (5.7 L)		
Battery	YTZ5S		
	12 V-3.5 Ah (10 HR)		
Gear ratios	1st	2.500	
	2nd	1.550	
	3rd	1.150	
	4th	0.923	
Reduction ratios (primary / final)	3.350 / 2.266		