

## LIGHTS/METERS/SWITCHES

### SPECIFICATIONS

ITEM		SPECIFICATIONS
Bulbs	Headlight (High/low beam)	12 V – 60/55 W
	Position light	12 V – 5 W
	Brake/taillight	12 V – 21/5 W × 2
	Turn signal light	12 V – 21 W × 4
	Instrument light	12 V – 1.7 W × 3
	Turn signal indicator	12 V – 1.7 W × 2
	High beam indicator	12 V – 1.7 W
	Neutral indicator	12 V – 1.7 W
	Oil pressure indicator	12 V – 1.7 W
	Side stand indicator	12 V – 1.7 W
Fuse	Main fuse	30 A
	Sub-fuse	10 A, 20 A
Thermosensor resistance	At 176 °F (80 °C )	47 – 57 Ω
	At 248 °F (120 °C )	14 – 18 Ω
Fan motor switch	Starts to close (ON)	208 – 216 °F (98 – 102 °C)
	Stops to open (OFF)	199 – 207 °F (93 – 97 °C)

### TORQUE VALUES

Thermosensor	12 N·m (1.2 kgf·m , 9 lbf·ft)	Apply sealant to the threads
Fan motor switch	18 N·m (1.8 kgf·m , 13 lbf·ft)	
Ignition switch mounting bolt	25 N·m (2.5 kgf·m , 18 lbf·ft)	
Neutral switch	12 N·m (1.2 kgf·m , 9 lbf·ft)	
Side stand switch bolt	10 N·m (1.0 kgf·m , 7 lbf·ft)	